

Incandescent Markers

Steady Burn or Flashing Fixtures

The incandescent OL2 and L-810 fixtures are used in all FAA Type A marking, as referenced in Advisory Circular (AC) 70/7460-1K, where double L-810 lighting is required.

Applications

- ◆ Telecommunication towers
- ◆ Broadcast towers
- ◆ Bridges
- ◆ MET towers
- ◆ Wind Turbines
- ◆ Water towers
- ◆ Buildings / Rooftops
- ◆ Airport taxiways
- ◆ Utility towers
- ◆ Cranes



Features/Benefits

- ◆ 1 year warranty
- ◆ Universal input power
- ◆ Operating temperature -55C to +55C
- ◆ Flash brand FREP power cable
- ◆ Fresnel optics
- ◆ No EMI or RF
- ◆ 24/7/365 Monitoring and Call Center services

Manufactured to specifications for: FAA Type L-810, FAA-AC 150/5345-43F, Transport Canada K310B, ICAO Annex 14 Low Intensity Type B, DGAC (Mexico)

Power Consumption

- ◆ 116w—Single red fixture
- ◆ 232w—Double red fixture

332 Nichol Mill Lane
Franklin, TN 37067



888-313-5274
flash.info@spx.com
www.flashtechology.com