



FTS 830

Current-Driven Unidirectional Approach Lighting



The FTS 830 is a current-driven unidirectional approach light that identifies runway end or the acquisition of an active runway. It can be used as a simple runway end identifier light (*REIL*) or as an addition to complete any number of approach light systems like MALS, MALS, SSALS, ALSF I and II for runway alignment and runway threshold marking.

The flashhead and power converter may be mounted together to form a single unit or separately to adapt to specific terrain needs.

STANDARD FEATURES

- Compatible with air-to-ground radio controllers and ground-to-ground remote systems
- Modular design for easy maintenance
- Longer flashtube life due to low voltage (± 500 VDC) required for operation
- Can be set for single-step or three-step intensity
- Conforms to FAA AC 150/5345-51, FAA Type L-849 Style A and E
- Complies with ICAO lighting regulations

FTS 830 Approach Lighting

OPTIONAL FEATURES

- Component-level technical training available
- 50 Hz and 60 Hz systems
- FTC 183 - Remote control and monitoring of approach lights
- FTC 435 - Automatically changes approach light intensity to match intensity of CCR controlled runway lights
- FTC 415 - Internal system controller

GENERAL SPECIFICATIONS

Flash Head - FH 800

Flash Rate	120 flashes per minute
Coverage	30° minimum horizontal coverage
Beam	10° minimum vertical beam
Elevation Angle	Adjustable elevation angle 0 to 25°
Weight	4 lbs (1.82 kg)
Dimensions	10.75 in. x 7.30 in. (226.06 mm x 198.1mm)

Certifications



Voltage Driven Power Converter - PC 830

Power		60 fpm	120 fpm
	High	135 W	190 W
	Medium	65 W	75 W
	Low	50 W	55 W
Current	2.8A to 6.6A		
Frequency	50/60 Hz		
Circuitry	Solid state circuitry		
Interlocks	Yes		
Internal Surge Protection	Yes		
Weight	21 lbs. (9.53 kg)		
Dimensions	12.25 in. x 19.44 in. x 13.44 in. 311.2 mm x 493.8 mm x 341.4 mm		

	High Intensity	Medium Intensity	Low Intensity
Standard	(20,000 Effective Candelas)	(2000 Effective Candelas)	(450 Effective Candelas)
	Nominal	Nominal	Nominal
	White	White	White
	(20,000 Effective Candelas)	(2,000 Effective Candelas)	(450 Effective Candelas)
Canadian	Nominal	Nominal	Nominal
	White	White	White



Bright Ideas. Brilliant Results.

Flash Technology
332 Nichol Mill Lane
Franklin, TN 37067-8203 USA

T +1 615 503 2000
T +1 888 313 5274
F +1 615 261 2600

flashtechnology.com



ISO 9001:2015

D8300-01 Rev B

Data and specifications subject to change without notification.

©2018 Flash Technology
All rights reserved.



SPX

SPX Corporation
Global Industrial Equipment
& Global Manufacturing
spx.com