


Marker Installation for the FTS 370 Vanguard®


The following guide provides installation steps for the LED marker provided with the FTS 370 Vanguard system. Verify the provided marker cable has a RED, BLACK, and bare DRAIN wire.

1. Open the access plate by loosening the (2) captive screws enough to swing the cover open and remove the installed wire nuts.

NOTE!! Do not remove the wire nut from the WHT/BLU wire.



2. Feed the marker cable through the black cord grip and strip approximately 1/4" from the jacket of each conductor. Cut off the the bare drain wire as this will not be used in the marker base.



3. Using the supplied wire nuts and electrical tape connect the (2) Red wires together and the (2) Black wires together.




4. Carefully place the wires inside the marker base and close the access plate. Ensure the screws and the cord grip are tight to prevent moisture intrusion.



Marker Installation for the FTS 371 Vanguard®

The following guide provides installation steps for the LED marker provided with the FTS 371 Vanguard Red only system. Verify the provided marker cable has a RED, BLACK, WHITE/BLUE and bare DRAIN wire.

1. Open the access plate by loosening the (2) captive screws enough to swing the cover open and remove the installed wire nuts.



2. Feed the marker cable through the black cord grip and strip approximately 1/4" from the jacket of each conductor. Cut off the the bare drain wire as this will not be used in the marker base.



3. Using the supplied wire nuts and electrical tape connect the (2) Red wires together, the (2) Black wires together, and the (2) White\Blue wires together..



4. Carefully place the wires inside the marker base and close the access plate. Ensure the screws and the cord grip are tight to prevent moisture intrusion.

